

1/3" Color CCD IR Camera – 25 Meter IR Range (30 LED)



Feature

- 1/3" SONY Color CCD
- IP-66 Water Resistance
- With 380 TV Lines Horizontal Resolution
- Lens 6mm (Optional 8mm / 12mm)
- Rapid Switch IR LED

SPECIFICATIONS

Model Number	K707-25M
Pick up device	1/3" interline transfer CCD
Total Pixels	NTSC: 537(H)x505(V) / PAL: 537(H)x592(V)
Effective Pixels	NTSC: 510(H)x492(V) / PAL: 500(H)x582(V)
Resolution	380 TV lines
Sync. System	2:1 Internal
Scanning System	NTSC: 525 Lines/30 frames; PAL: 625 Lines/25 frames
S/N Ratio	More than 48dB (AGC OFF)
Electronic Shutter	Auto; (1/60-100,000 sec)NTSC; (1/50-100,000 sec)PAL
Min. Illumination	0.4 Lux / F2.0 (0 Lux at IR On)
Video Output	1.0 Vp-p / 75 ohm composite
Water Resistance	IP66
IR Distance	More than 25M (30 pcs IR LED)
IR trigger	3.1Lux/3.7Lux IR ON/OFF
Power Supply	12V +/- 10%
Power Consumption	9.2W (Max)
Current	770mA
Dimension	80mm(Diameter) x 161mm(L)
Operation Temperature	-10 to 50°C (14 to 122°F)