

AAC-900 Pan/Tilt Analog (CCTV) Camera



Features

- Compact size and light-weight
- Cost effective and easy to install
- Wide-range Pan/Tilt operation
- RS-485 Remote Control
- Use "Pelco D" protocol; work with most of DVRs and Video Servers
- Camera ID setting (1~254)
- High quality 1/3" CCD sensor
- Included ceiling mount kit
- IR remote control available (option)

Specification

Model	AAC-900
Image sensor	1/3" Color CCD
Picture Elements	NTSC: 512*492/ PAL: 512*582
Horizontal Resolution	380 TV Lines
Scanning System	NTSC, PAL, 2:1 Interlaced
H. Sync Frequency	NTSC: 15.734 KHz, PAL: 15.625 KHz
V. Sync Frequency	NTSC: 59.94 KHz, PAL: 50 KHz
Synchronization	Internal
Minimum Illumination	1.0 Lux at F2.0
Back Light Compensation	AUTO
Electronic Shutter	AUTO, Range: 1/50(1/60) ~ 1/100,000 sec.
Auto Gain Control	AUTO
Video Output	1 Vp-p, 75 Ohms
Lens	Standard: 6mm/F1.8
Pan Angle	-135° ~ +135°
Tilt Angle	-90° ~ +45°
Control Interface	RS-485
Address Setting	1~254
Dimensions	115mm(L) * 105mm(W) * 114mm(H)
Weight	Net. 308g.
Power	12V DC
EMI & Safety	CE, FCC